

(12) United States Patent

Sheerer et al.

(10) Patent No.:

US 6,375,796 B1

(45) Date of Patent:

Apr. 23, 2002

(54) METHOD OF TREATING MATERIAL IN A CONTINUOUS DIGESTER

(75) Inventors: Jay K. Sheerer, Hudson Falls; Joseph

R. Phillips, Queensbury, both of NY (US); Jerry R. Johanson, San Luis Obispo, CA (US); John Pietrangelo,

Queensbury, NY (US)

(73) Assignee: Andritz Inc., Glens Falls, NY (US)

Subject to any disclaimer, the term of this (*) Notice:

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

Appl. No.: 09/640,666 (21)

(22)Filed: Aug. 18, 2000

Related U.S. Application Data

Division of application No. 08/953,880, filed on Oct. 24, 1997, now Pat. No. 6,129,816.

Int. Cl.⁷ D21C 7/00; D21C 3/26; D21C 7/14

U.S. Cl. 162/19; 162/17; 162/237; 162/251; 162/248; 162/243

Field of Search 162/237, 251, 162/17, 19, 248, 249, 243, 37, 39, 40, 41,

42-45, 60; 422/218, 239, 292

(56)References Cited

U.S. PATENT DOCUMENTS

2,634,209 A 4/1953 Nevin 6/1953 Ross et al. 2,640,774 A 2,661,095 A 12/1953 Koth

2,845,347 A 7/1958 Byrne 8/1961 Lang 2,998,064 A 3,385,753 A 5/1968 Rich 3,397,110 A 8/1968 Rosenblad 10/1972 Rich 3,700,548 A 8/1993 Ekholm et al. 5,234,550 A

FOREIGN PATENT DOCUMENTS

CA 807926 3/1969 2/1995 950826

Primary Examiner—Stanley S. Silverman Assistant Examiner—Dionne A. Walls (74) Attorney, Agent, or Firm-Nixon & Vanderhye P.C.

ABSTRACT

A comminuted cellulosic fibrous material treatment vessel assembly includes a substantially vertical vessel having a top, bottom, and outlet, and through which the material flows in a flow direction. The vessel preferably has a substantially cylindrical wall with at least one diameterchanging transition between the inlet and the outlet. A screen assembly is preferably provided at or just past the transition. The screen assembly comprises one or more annular screen surfaces diverging in the flow direction of the material, the angle of divergence being between about 0.5-10° to the vertical, and preferably substantially continuous. Providing such a screen assembly reduces the radial compression of material thereon, and increases the volume and rate of liquid that can flow through the material and be removed through the screen surface compared to a non-diverging screen surface (that is a right-cylindrical surface). The screen surface has openings of substantially uniform size, and preferably with a substantially uniform percentage of open area, in the flow path.

17 Claims, 4 Drawing Sheets

